Technical Data for: 2019/1495

Triumph TR6, chassis (commission) number CF/57913-U

Engine	Four stroke, overhead valves, side
•	cam shaft, crank shaft with integral
	balance weights and four main bearings
Number of cylinders	Six in line
Firing order	1-5-3-6-2-4
Bore and stroke	74.7 mm x 95 mm
Cubic capacity	2498 cc
Compression ratio	7.5:1
Fuel system	Evaporative emissions control: fuel tank vapour emissions vented via separator canister to
•	charcoal canister, Stromberg 2 x 175 CDSEV carburettors, exhaust emissions controlled
Emissions	Emissions conforming to US Federal State air
Litigatoria	pollution standards at the time of production
Gearbox	Four speed, synchromesh
Ratio in fourth	1.0
Ratio in third	1.39
Ratio in second	2.10
Ratio in first	2.99
Ratio in reverse	3.37
Clutch	Borg and Beck 8 1/2 inch diaphragm spring
Rear axle	Semi-floating axle shafts, three piece casing
Rear axle ratio	3.70:1
Brakes	Hydraulic on all four wheels
Front	276 mm diameter caliper disc
Rear	228 x 44.5 cm drum (leading and trailing shoes)
Servo	Direct acting servo providing 2.2:1 nominal boost
Steering	Alford and Adler, rack and pinion unit
Turning circle	34 ft (10.4 m)
Wheels	Steel disc 5 ½ J x 15 inch
Tyres	185 x 15 Michelin X radial ply
Suspension	
Front	Low periodicity independent system. Coil spring and telescopic dampers
Rear	Semi-trailing arm independent, with coil springs
<u></u>	and piston damper
Dimensions	•
Track front	50 1/4 inch (1276 mm)
Track rear	49 3/4 inch (1264 mm)
Wheelbase	88 inch (2240 mm)
Overall length	163.6 inch (4155 mm)
Overall width	58 inch (1470 mm)
Overall height	.50 inch (1270 mm)
Weight	, , , , , , , , , , , , , , , , , , ,
Kerb basic	2438 fb (1106 kg)
Complete (including fuel, oil, water, tools)	1190 lb (1016 kg)
Maximum gross	3042 lb (1380 kg)
Vehicle capacity weight	434 lb (197.3 kg)
Body and chassis	
Type of construction	Separate chassis and body
Material of body panels	All steel
Number of costs	Two

All technical data published by the manufacturer for the model mentioned Signed on behalf of BMIHT

Number of seats

Windscreen glass

* Triple SU's replaced Stromberg 2x175 carbs

Two

Laminated