
SERVICE  TOOLS

18G304A

BOLT ADAPTOR— $\frac{1}{2}$ in. UNF

Three adaptor bolts are required for use with basic tool 18G304 on each model.

Morris

Oxford (Series SMO) from Chassis No. 97795, Six (Series SMS) from Chassis No. 11345, $\frac{1}{2}$ -ton Van (Series MCV) from Chassis No. 8967.

Wolseley

Four-Fifty from Chassis No. 10533, Six-Eighty from Chassis No. 15138.

M.G.


Series YB from Chassis No. 0286, TD from Chassis No. 12285, TF.

Austin Trucks

Series 101, 152.

Morris Trucks

J, JB, J.2.



18G304B

BOLT ADAPTOR— $\frac{7}{16}$ in. UNF

* Two adaptor bolts are required for use with basic tool 18G304 on these models; three adaptor bolts are required for the remainder.

Morris

Cowley*, Cowley 1500*, Oxford (Series II*, III*, and IV*), Isis, Isis (Series II), $\frac{1}{2}$ -ton Van (Series III).

Wolseley

Four-Fortyfour*, Fifteen-Fifty, Six-Ninety, Six-Ninety (Series II and III).

M.G.

'MGA', Magnette*.

Riley

Pathfinder, Two-Point-Six.

Austin Trucks

Series 152.

Morris Trucks

J.2.



18G304C

BOLT ADAPTOR— $\frac{7}{16}$ in. UNF

Two adaptor bolts are required for use with basic tool 18G304 on the following models.

Morris

Minor (Series MM) from Chassis No. 131858, Minor (Series II and 1000) up to Chassis No. 228266 approximately.

